

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



B13

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 88/16	A1	(11) International Publication Number: WO 99/35058
		(43) International Publication Date: 15 July 1999 (15.07.99)

(21) International Application Number: PCT/GB99/00037

(22) International Filing Date: 6 January 1999 (06.01.99)

(30) Priority Data:
9800149.8 7 January 1998 (07.01.98) GB


(71)(72) Applicant and Inventor: JARDINE, Mark, Hamilton
[GB/GB]; Grove Farm, Creeting St. Peter, Needham
Market, Ipswich IP6 8QG (GB).

(74) Agents: GEMMELL, Peter, Alan et al.; Dummett Copp, 25
The Square, Martlesham Heath, Ipswich IP5 3SL (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP,
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK,
MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU,
ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG,
ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI,
FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE,
SN, TD, TG).

Published
With international search report.

(54) Title: A BAG



(57) Abstract

A collapsible bag (2) for the storage and transport of bulk materials comprises a bottom panel (13), a plurality of side panels (11, 12), and a pair of substantially parallel tubular guide members (4). The guide members (4) are secured on or adjacent to the tops of at least some of the side panels (11, 12). The tubular members (4) are resilient and connected together by rigid spacing means (22) at or adjacent to their ends. The invention also provides a method for manufacturing the bag and a device for modifying a conventional bag to make a bag in accordance with the invention.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

A BAG**BACKGROUND OF THE INVENTION**

5 1. Field of the Invention.

 The present invention relates to a bag,
particularly to a bag for bulk storage and transport of
materials, notably particulate solids materials. The
invention also provides a device for modifying
10 conventional bags.

2. Description of the Prior Art

 Bags for storage and transport of bulk materials,
for example half-tonne, one-tonne, or two-tonne
15 capacity bags, are typically of generally cuboid shape,
formed from a fabric material such as polypropylene.
Typically, the weight of fabric material will be from
about 180 g/m² to 400 g/m² depending on the intended load
and operating conditions. The fabric may be reinforced
20 for extra strength.

 The bags have a top which is either permanently fully
open or which can be opened, for loading. The bottoms
of the bags are typically provided with a discharge
25 spout through which the contents of the bag can be
emptied when the spout is opened. Alternatively, the
base of the bag may be openable for discharge of the
contents.

30 To enable such bags to be lifted and manoeuvred by a
fork-lift truck, each bag is typically provided with a
lifting loop at each corner. To lift a filled bag, a
fork-lift operator brings the tines of the fork close
to the top of one edge of the filled bag so that each
35 tine is adjacent to a lifting loop. An assistant lifts
up each lifting loop to enable a tine to pass through

- 2 -

the loop while the operator moves the tines forward over the bag. The fork-lift operator moves the tines further over the top of the bag until the tines are adjacent the rear pair of lifting loops, and the
5 process is repeated so that the tines are disposed through the rear lifting loops. The bag can then be lifted and moved.

A problem with this procedure is that there is a danger
10 of injury to the assistant when the tines or the fork are moved. This is a particular problem when filled bags are stacked high, on top of each other. The fork-lift operator is unable to see the rear pair of lifting loops when the stack is too high, and the assistant may
15 be injured by a tine or pushed off a ladder. It is also costly to employ two men to secure the bag on the fork.

If no assistant is present, the fork-lift operator must
20 move the truck so that the tines of the fork are positioned near the front loops. He must then get out of the cab of the truck, hook the front loops over the tines, and get back in the cab. He must then drive the truck forward as far as he thinks necessary, get out
25 again, hook the rear loops onto the tines (if he has judged the forward distance correctly), get back in the cab, drive further forward to pick up the bag. The procedure is slow and can be dangerous.

30 To reduce the load to which lifting loops are subjected it has been proposed to provide bags with integral lifting slings along opposite top edges so that the load is spread out along those edges; see for example GB 1 549 448, GB 2 050 298, and GB 2 092 990. However,
35 the use of such slings does not remove the need for a fork-lift operator either to leave the cab of his truck

- 3 -

or to use an assistant to hook the tines of the fork-lift in the slings.

SUMMARY OF THE INVENTION

5

According to an aspect of the present invention there is provided a collapsible bag for the storage and transport of bulk materials, as specified in Claim 1

- 10 Another aspect of the invention provides a collapsible bag for the storage and transport of bulk materials as specified in Claim 10.

Resilient tubular members function as guides for the
15 tines of a fork-lift so that, once the tines have been inserted into one end of the tubular member, full insertion of the tines through the tubular members can be accomplished without an assistant and without the need for a fork-lift truck operator to leave the truck.

20

Because the tubular members are resilient, they lie flat when under load, for example when other filled bags are stacked on top, but revert to a predetermined sectional shape when the load is removed. This allows
25 stacking of bags without significant wasted space, and permits lifting and moving of the bags by a fork-lift operator without an assistant.

Rigid connection of tubular members ensures that they
30 are spaced apart from each other by a predetermined distance so that the tines of a fork, suitably spaced apart, can be inserted into the tubular members without undue difficulty. The term "rigid" is used herein to denote a linkage which is sufficiently stiff to
35 maintain the necessary separation between the tubular members. The skilled person will therefore appreciate

- 4 -

that the spacers therefore need not be totally unyielding, particularly where the tubular members are dimensioned to allow some tolerance for receiving the tines of a fork-lift. The spacers may be made from any
5 suitable structural material. Suitable materials include metals or structural plastics materials, for example nylon or an injection-moulded plastics material.

10 The tubular members may carry load along their length when the filled bag is suspended, or strong points in the tubular members may take the load of a filled bag, so that other regions of the tubular members need not be substantially load carrying.

15 The tubular members may be secured in relation to the top edges of at least some of the side panels by direct attachment to the edges, for example by sewing, gluing or riveting, or they may be formed integrally with the
20 edges as will be further described below.

Alternatively, the tubular members may be secured in relation to the edges by means of lifting loops on a conventional bag.

25 In a particularly preferred embodiment, the bag is formed from a conventional bag with a lifting loop at each corner, by fitting an insert to the bag and securing it by means of the lifting loops. The insert
30 comprises a pair of substantially parallel resilient tubular members which are connected together at or adjacent to each end by rigid spacing means. To provide strong points, it is preferred that the tubular members have laterally extending slots or apertures on
35 their upper surfaces for receiving the lifting loops, and the tubular members are of sufficient size that at

- 5 -

least the top portion of each loop is disposed inside a tubular member when the insert is fitted on the bag. The tubular members thus function as guides for the tines of a fork-lift, but the lifting loops take the
5 load when the bag is lifted on the tines.

Accordingly, another aspect of the present invention comprises a device for securing to a bag for the storage and transport of bulk materials, as specified
10 in Claim 11.

The tubular members may be made from any suitable resilient material, for example a natural or synthetic rubber material. A preferred material is vulcanised
15 rubber, or the sort of rubber that wellington boots are typically made from.

The inside surfaces of the tubular members may optionally be provided with a tough coating to confer
20 resistance to cutting and scratching by the tines of a fork-lift.

It will be appreciated that the tubular members may be of any cross sectional shape which will accept the
25 tines of a fork-lift or the like. For example the tubular members may be circular, rectangular, square or oval in cross section. For convenience hereinafter, the invention will be described with reference to tubular members which are substantially circular in
30 section. However, it is to be understood that the invention is not limited to this embodiment.

The tubular members may be of any suitable diameter to receive a tine of a fork-lift, for example they may
35 have a diameter in the range 100 to 300 mm, notably about 200 mm.

- 6 -

Although it is preferred to make the bag by modifying an existing conventional bag as described above, the bags can be made by other methods. For example, the tubular members may be manufactured separately and subsequently secured to opposite top edges of the box by securing means, for example stitching. The rigid connecting means may be secured to the tubular members either before or after the tubular members are secured to the edges of the box. In another embodiment, the tubular members are formed from the material of the bag so that the tubular members are integral parts of the bag. This may be achieved, for example, by forming the bag with a pair of opposed sides which are longer than the other pair of opposed sides, and forming the extra length into tubes. A preferred material is polypropylene fabric. The tubular members may be reinforced by incorporation of a rubber material, to impart resilience. The rubber material may be secured to the tubular members by any suitable securing means, for example stitching or gluing.

Accordingly, a further aspect of the invention provides a method of manufacturing a collapsible bag for the storage and transport of bulk materials as specified in Claim 13.

Resilience may also be imparted by reinforcing the tubular member with a suitable reinforcing member, for example a wire of metal or plastics material which is helically wound around the tubular member.

Additionally or alternatively, the tubular members may be placed on a former to define a preferred shape and/or configuration, and sprayed with a fluid material that dries to a form-retaining coating to retain them

- 7 -

in that preferred shape and/or configuration. The fluid material may be a foam or a lacquer.

BRIEF DESCRIPTION OF THE DRAWINGS

5

The invention will now be further described, by way of example, with reference to the following drawings in which:

10 Figure 1 is a view of a bag in accordance with one aspect of the present invention;

Figure 2 shows a stage in the manufacture of the bag of Figure 1;

15

Figure 3 is a perspective view of a device for modifying a conventional bag; and

20 Figure 4 shows the device of Figure 3 mounted on a bag, being lifted by a fork-lift.

DETAILED DESCRIPTION OF THE INVENTION

25 The collapsible bag 2 is formed from a structural fabric, in this example, polypropylene fabric of weight 300 g/m². The weight of fabric used will, of course, depend on the maximum load which is to be carried by the bag 2. Methods of assembling suitable fabrics into a bag capable of carrying a load of particulate solids materials 8 are well known to those skilled in the art.

35 The bag 2 is of a cuboid shape with a generally square plan section bottom panel 13. The bottom panel 13 will have a discharge spout (not shown) for emptying the contents. The bag 2 has pairs of opposed side walls 11, 12. Opposed walls 12 of the bag 2 have top edges 14,

- 8 -

each of which is provided with a tubular member 4 secured to the edge 14 and extending along a substantial length thereof. In this example a tubular member 4 is disposed along the entire length of each top edge 14.

Each tubular member 4 is provided with a pair of straps 10 which are secured to the inner surface of the opposed walls 12 by securing means, in this example, stitching.

The tubular members 4 are connected together by a pair of substantially rigid spacers 22 which serve to maintain the tubular members 4 in a configuration wherein their longitudinal central axes are substantially parallel. Thus if the tine of a fork-lift is inserted into an end opening 6 of each tubular member 4 so that the longitudinal axis of the tine is substantially parallel to or collinear with the longitudinal central axis of the tubular member 4, the tine may be pushed forwards through the tubular member 4 to its fullest extent.

The tubular members 4 are resilient, so that they adopt a substantially circular cross sectional configuration in the absence of an applied load. This ensures that each tubular member 4 is open to receive a tine of a fork-lift when the bag 2 is on top of a pile.

A fork-lift operator can insert the tines of his fork-lift into the tubular members 4, lift, move, and lower the filled bag 2, and remove the tines of the fork from the tubular members 4, without leaving his cab and without external assistance.

35

Figure 2 shows one step in a method of manufacturing

- 9 -

the bag 2. The bag is fabricated by well known methods, but leaving one pair of opposed walls 12 with an additional length of fabric in the form of a flap 18. Each flap 18 is secured along a line defining an edge 14 by securing means, in this example by stitching, as shown by the arrows. The straps 10 are sewn to the insides of the respective opposed walls 12 for reinforcement.

10 A rubber sheet 16 is secured to each tubular member 4, formed from the flap 18, by suitable securing means, for example gluing or stitching. The rubber reinforcement 16 imparts resilience to the tubular member 4.

15 Finally, the tubular members 4 are connected together at each end by a pair of substantially rigid spacer rods 22, in this example made of nylon, which are secured to the tubular members 4 by any suitable fixing means, for example by means of glue.

For simplicity, only a single rubber sheet 16, a single rod 22, and a single pair of reinforcing straps 10 are illustrated, but it is to be understood that in this example the finished bag is substantially symmetrical about either central vertical plane normal to a wall of the bag.

Turning now to Figure 3, a device for modifying a conventional bag with a lifting loop at each corner comprises a pair of substantially parallel resilient tubular members 4 connected together by a pair of rigid spacing rods 22 adjacent each end. The rods need to be spaced sufficiently far apart to permit filling of a bag through an area between them when the device is mounted on a bag. Each tubular member 4 is provided

- 10 -

- with a lateral slot or cut-out portion 24, through which a lifting loop of a bag will be disposed. The slot 24 is here shown having a long axis normal to the long axis of the tubular member 4. It will be understood that the slots may be other shapes and orientations providing that sufficient lateral access is presented for a lifting loop to be retained in the slot when appropriately presented.
- 10 Figure 4 shows the device of Figure 3 in use, mounted on a conventional bag 2 with a strap or lifting loop 26 at each top corner. Each lifting loop 26 is disposed around a tubular member 4 and locates in a cut-out portion 24. The tines 28 of a fork-lift can readily enter the tubular members 4 and the weight of the bag is supported entirely by the lifting loops 26. The tubular members 4 act as guides for the tines 28 but do not support load. The ends of the tubular members 4 project beyond the edges of the bag 2, so that if a plurality of bags are stacked on top of each other, the middle regions of the resilient tubular members 4 are squashed by the resulting load, but the ends remain open. The end portions of the tubular members 4 therefore always retain the preferred sectional shape regardless of whether the middle of the tubular members 4 are squashed, and this helps the tubular members 4 to return quickly to their tubular shape when a load is removed.
- 30 The invention provides a bag which can be moved and lifted by a single fork-lift truck operator without external help. Filled bags can be moved more safely than conventional bags, and with less manpower.
- 35 Although the invention has been described with reference to one pair of tubular members, it is to be

- 11 -

understood that the invention is not limited to this embodiment. It would also be possible to provide a tubular member along each top edge of the bag, to allow a fork-lift to engage with the bag from any of four
5 directions.

- 12 -

CLAIMS

1. A collapsible bag (2) for the storage and transport of bulk materials, comprising a bottom panel (13), a plurality of side panels (11, 12), and a pair of substantially parallel tubular guide members (4) secured on or adjacent to the tops of at least some of the side panels (11, 12), characterised in that the tubular members (4) are resilient and connected together by rigid spacing means (22) at or adjacent to their ends.
2. A bag (2) as claimed in Claim 1, wherein the tubular members (4) are secured to at least one of the side panels by means of straps (26).
3. A bag (2) as claimed in Claim 2, wherein the upper surface of each tubular member (4) is provided with a slot or cut-out portion (24) adjacent each end, a strap (26) being received in each slot (24) and at least the top portion of each of the said straps (26) being disposed inside a tubular member (4), so that when the tines of a fork-lift truck are inserted into the tubular members (4) under the top portions of the straps (26) and lifted, the weight of the bag (2) will be carried by the straps (26).
4. A bag (2) as claimed in any one of the preceding claims, wherein each tubular member (4) is disposed along substantially the entire length of the top edge (14) of a side panel (12).
5. A bag (2) as claimed in Claim 4, wherein the tubular members (4) extend longitudinally beyond the edges (14) of the side panels (12) along which they are disposed.

- 13 -

6. A bag (2) as claimed in any one of the preceding claims, wherein the tubular members (4) are reinforced with a rubber material (16).

5

7. A bag (2) as claimed in any one of the preceding claims, wherein the tubular members (4) are reinforced with a wire of metal or a plastics material which is helically wound around each tubular member.

10

8. A bag (2) as claimed in any one of the preceding claims, which is of generally square or rectangular plan section.

15 9. A bag (2) as claimed in any one of the preceding claims, wherein the bag (2) may be lifted by means of the tubular members (4).

10. A collapsible bag (2) for the storage and
20 transport of bulk materials, the bag having a generally square or rectangular plan section and being provided with a pair of tubular members (4) each secured to and disposed along a substantial length of an opposite top edge (14) thereof whereby the bag (2) may be lifted by
25 means of the tubular members (4), characterised in that the tubular members (4) are resilient and connected together by rigid spacing (22) means at or adjacent to their ends.

30 11. A device for securing to a collapsible bag for the storage and transport of bulk materials comprising a bottom panel (13), a plurality of side panels (11, 12), and a plurality of straps or lifting loops (26) for lifting the bag, the device comprising a pair of
35 substantially parallel resilient tubular guide members (4) which are connected together at or adjacent to each

- 14 -

end by rigid spacing means (22).

12. A device as claimed in Claim 11, wherein each tubular member (4) has a slot or cut-out portion (24) adjacent each end for receiving a portion of a strap or lifting loop of a bag.



13. A method of manufacturing a bag for the storage and transport of bulk materials, the bag having a bottom panel (13) and a plurality of side panels (11, 12) and being provided with a pair of substantially parallel tubular members (4) each secured to and disposed along the top edges (14) of a pair of opposed side panels (12); the method comprising forming the bag with one pair of opposed sides (12) which are longer than the other sides (11), securing the free end of each extra-length side (12) to that side so as to form a tubular member (4), providing each tubular member (4) with a resilient reinforcement (16) and connecting the tubular members (4) together at or adjacent each end by substantially rigid connecting means (22).

14. A method as claimed in Claim 13, wherein the resilient reinforcement comprises a rubber reinforcing member (16).

15. A method as claimed in Claim 13, wherein the resilient reinforcement is provided by placing each tubular member (4) on a former to define a preferred shape and/or configuration and spraying the tubular member (4) with a fluid material that dries to a form-retaining coating to retain it in that preferred shape and/or configuration.

16. A method as claimed in claim 15, wherein the fluid material is a foam or lacquer.

1/2



2/2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/00037

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B65D88/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 259 230 A (MECAROUTE) 9 March 1988 see column 3, line 19 - column 4, line 20; figures 1-5 ---	1,2,4,5, 8-11
X	FR 2 721 304 A (MECAROUTE) 22 December 1995 see page 3, line 4 - page 4, line 36; figures 1-3 ---	1,2,4,5, 8-11
A	GB 2 092 990 A (A.S. NYBORG PLAST) 25 August 1982 cited in the application see page 2, line 32 - line 101; figure 1 ---	1,13
A	FR 2 608 138 A (SHELL CHIMIE) 17 June 1988 see figures 1A-6 ---	1
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

19 April 1999

Date of mailing of the international search report

26/04/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Berrington, N

INTERNATIONAL SEARCH REPORT

Int. lional Application No

PCT/GB 99/00037

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 37908 A (SOUTHCORP AUSTRALIA) 16 October 1997 see figures 1-11 ----	1
A	FR 1 443 272 A (SAINT FRÈRES) 16 May 1966 see page 2, left-hand column, line 14 - line 44; figures 1,2 ----	1,13
A	FR 2 306 134 A (PEDELUCQ) 29 October 1976 see figures 1-4 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/00037

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0259230 A	09-03-1988	FR 2603259 A AT 65975 T AU 7777387 A DE 3771971 A DK 457487 A FI 873806 A JP 63134499 A US 4792171 A	04-03-1988 15-08-1991 10-03-1988 12-09-1991 04-03-1988 04-03-1988 07-06-1988 20-12-1988
FR 2721304 A	22-12-1995	NONE	
GB 2092990 A	25-08-1982	DK 63881 A BE 892124 A DE 3205011 A FR 2499944 A NL 8200572 A SE 448081 B SE 8200817 A	14-08-1982 27-05-1982 09-09-1982 20-08-1982 01-09-1982 19-01-1987 14-08-1982
FR 2608138 A	17-06-1988	NONE	
WO 9737908 A	16-10-1997	AU 2145397 A	29-10-1997
FR 1443272 A	05-10-1966	NONE	
FR 2306134 A	29-10-1976	NONE	